




FS Damero

Single fired floor tiles

FS Damero-N



FS Damero

Single fired floor tiles

FS Rombos-N



FS-0

13 patterns




FS DAMERO-N

13 patterns



FS ESPIGA


3 patterns



FS ROMBOS-N

4 patterns

FS DAMERO



45 * 45 * 1,05 cm | 18 * 18"

NO RECTIFIED	NATURAL
PREC. CODE BN14	
FS DAMERO-N	15077
FS-0	13305
FS ESPIGA	15816
FS ROMBOS-N	16447



Rodapie - Skirting (R.FS 0)
8 * 45 cm | 3 * 18" P8

CARACTERÍSTICAS TÉCNICAS TECHNICAL CHARACTERISTICS			
joint 1,5 mm	versatile	matt	diferent shades
shade variation V3	various graphics	various moulds	

CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO ANTI-SLIP CHARACTERISTICS		
Ensayo Essay	Características Features	Resultado Result
DIN 51130	Ángulo crítico (Pies calzados) Critical angle (footwear)	R9
BS 7976-2	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test-PTV)	+36 Wet
UNE-ENV 12633	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	Class 1
ISO 10545-7	Resistencia a la Abrasión Superficial/ Resistance to Surface Abrasion	4

EMBALAJE PACKING		(Los pesos aquí reflejados pueden sufrir ligeras variaciones en función del lote de producción. Weights shown here may slightly vary depending on the production lot.)							
Formato Sizes	Cajas Boxes	Pallet			Cont./20' 21500 kg.	Cont./20' 24000 kg.	Pallet		
		Cajas	m ² / sq.m	kg			Tamaño cm aprox.	m ² / sq.m	m ² / sq.m
cm	Piezas	m ² / sq.m	kg	Cajas	m ² / sq.m	kg	Tamaño cm aprox.	m ² / sq.m	m ² / sq.m
45 * 45 * 1,05	5	1	23,139	66	66	1551	120 * 80 * 105	914,89	1021,28
inch	Units	ft ²	lb	Boxes	ft ²	lb	Sizes inch approx.	ft ²	ft ²
17 11/16 * 17 11/16 * 7/16	5	10,76	51,02	66	710,42	3419,96	47 1/4 * 31 1/2 * 41 5/16	9847,91	10993,02